

GPU / XEON PHI

UP TO 2 GPU's IN 1U

Key Features :

- ❖ Single socket P (LGA 3647) supports Intel® Xeon® Scalable Processors
- ❖ Up to 768GB ECC 3DS LRDIMM, up to DDR4-2666MHz; 6 DIMM slots
- ❖ 2 PCI-E 3.0 x16 slots (support double-width GPU), 1 PCI-E 3.0 x16 low-profile slot (center right)
- ❖ 2x 10GBase-T LAN ports via Intel X550
- ❖ Dual M.2 Mini-PCIe support 2280
- ❖ 8 Heavy duty 4cm counter-rotating 4cm fans with air shroud & optimal fan speed control
- ❖ 1400W High-efficiency Power Supply Platinum Level (94%+)

Notes :

- ✓ 1019GP-TT : 6 Hot-swap 2.5" SAS/SATA drive bays
- ✓ 5019GP-TT : 3 Hot-swap 3.5" SAS/SATA drive bays, 1 slim DVD-ROM drive bay



SYS-1019GP-TT



SYS-5019GP-TT

GPU / XEON PHI

UP TO 4 GPU's IN 1U

Key Features :

- ❖ Dual socket P (LGA 3647) supports Intel® Xeon® Scalable Processors, 3 UPI up to 10.4GT/s
- ❖ Up to 1.5TB ECC 3DS LRDIMM, up to DDR4-2666MHz; 12 DIMM slots
- ❖ 4 PCI-E 3.0 x16 (FHFL), 1 PCI-E 3.0 x16 (LP) and 1 PCI-E 3.0 x8 (LP)
- ❖ 2x 10GBase-T LAN ports via Intel X540
- ❖ 9 Heavy duty 4cm counter-rotating fans with air shroud & optimal fan speed control
- ❖ 2000W Redundant Power Supplies Titanium Level (96%)

Notes :

- ✓ 1029GQ-TRT : 2 Hot-swap 2.5" SAS/SATA drive bays, 2 Internal 2.5" drive bays
- ✓ 1029GQ-TNRT : 2 Hot-swap 2.5" SAS/SATA/NVMe drive bays, 2 Internal 2.5" drive bays



SYS-1029GQ-TRT



SYS-1029GQ-TNRT

GPU / XEON PHI

UP TO 4 GPU_s

Key Features :

- ❖ Dual socket P (LGA 3647) supports Intel® Xeon® Scalable Processors, 3 UPI up to 10.4GT/s
- ❖ Up to 2TB ECC 3DS LRDIMM, up to DDR4-2666MHz; 16 DIMM slots
- ❖ 6 PCI-E 3.0 x16 slots, 1 PCI-E 3.0 x4 (in x8 slot)
- ❖ 8 Hot-swap 3.5" drive bays
- ❖ 2x 10GBase-T LAN ports via Intel X550
- ❖ 1 VGA, 2 COM, 5 USB 3.0
- ❖ 4 Heavy duty fans, 4 exhaust fans, and 2 active heatsink with optimal fan speed control
- ❖ 2200W Redundant Power Supplies Titanium Level (96%)
- ❖ GPU Kit for passive GPU/Coprocessor support (MCP-320-74702-0N-KIT)



SYS-7049GP-TRT

GPU / XEON PHI

UP TO 4 NVIDIA TESLA P100 SXM2 GPU_s

Key Features :

- ❖ Dual socket P (LGA 3647) supports Intel® Xeon® Scalable Processors, 3 UPI up to 10.4GT/s
- ❖ Up to 1.5TB ECC 3DS LRDIMM, up to DDR4-2666MHz; 12 DIMM slots
- ❖ 4 PCI-E 3.0 x16 slots
- ❖ 2 Hot-swap 2.5" SAS/SATA drive bays, 2 Internal 2.5" drive bays
- ❖ 2x 10GBase-T LAN ports via Intel X540
- ❖ 7 Heavy duty 4cm counter-rotating fans with air shroud & optimal fan speed control
- ❖ 2000W Redundant Power Supplies Titanium Level (96%)



SYS-1029GQ-TXRT